



● Specifications

General Characteristics		Modes		Key Features	
Material	Zinc alloy(Body) Tempered glass(Front panel)	Operation mode	Manual mode Auto mode	Lock	Indoor deadlock System lock
Finishing	Electroplating	System unlock mode	General mode Dual verification mode	Safety	Hidden PIN code Outside forced lock mode Dual verification
Color	Copper/Black/Golden			Alarm	Anti-prying alarm Outside forced lock alarm Abnormal latch bolt alarm
Handle	Push-pull handle	Electrical Power	Working power supply	4 AA batteries	
Mortise	Full auto mortise C-grade lock cylinder	Battery life	10 months		
Fingerprint sensor	Semiconductor sensor	Emergency power supply	5V power bank	Remote controlling	Unlock when link with smart door viewer Add PIN codes Door lock parameter settings
Connection	Gateway	Operating Environment	Working voltage	4.5-6V	
Access Solution		Static working current	<110uA(With gateway)		
Outside unlocking	Fingerprint PIN code Card Mechanical key App	Dynamic working current	<50mA(With gateway)	Emergency escape	Indoor fast opening mortise
Inside unlocking	Handle Button Infrared induction	Temperature	-20°C~+60°C	Update	OTA or serial interface update
Capacity		Humidity	15%RH-93%RH	Indicator	Low battery indication Lock status indication Mute status indication System lock indication Outside forced lock indication Indoor infrared unlocking indication Open/Close infrared unlocking indication
Fingerprint	100	Installation Requirements	Door thickness	38-60mm 60-90mm 90-120mm	
Card	100			Other range*	
Master PIN code	1	Door opening direction	Left-in/Left-out/ Right-in/Right-out	Voice guide	Human voice guide
User PIN code	10				
One-time PIN code	1	Door type	Wooden/Copper/Security door		

*10 months: May be less depending on actual usage.

*Other range: Please consult our service agent or an authorized dealer.